



Specifications

Nominal Voltage		12 V
Rated capacity(20HR)		20Ah
Dimension	Length	181 ± 2mm (7.13inch)
	Width	77 ± 1mm (3.03inch)
	Height	167 ± 2mm (6.57inch)
	Total Height	167 ± 2mm (6.57inch)
Approx. Weight		5.5kg (12.1lbs) ± 4%

Dimensions



Terminal



Characteristics

Capacity (25°C)	20HR(10.5V)	20Ah
	10HR(10.5V)	17.8Ah
	1HR(9.60V)	12.7Ah
Terminal type		T3/T12
Internal resistance (Fully charged, 25°C)		Approx. 15mΩ
Capacity affected by temperature (20HR)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-discharge (25°C)	3 month	Remaining Capacity: 91%
	6 month	Remaining Capacity: 82%
	12 month	Remaining Capacity: 65%
Nominal operating temperature		25°C ± 3°C (77°F ± 5°F)
Operating temperature range	Discharge	-15°C ~ 50°C (5°F ~ 122°F)
	Charge	-10°C ~ 50°C (14°F ~ 122°F)
	Storage	-20°C ~ 50°C (-4°F ~ 122°F)
Float charging voltage(25°C)		13.50 to 13.80V Temperature compensation: -18mV/°C
Cyclic charging voltage(25°C)		14.50 to 15.00V Temperature compensation: -30mV/°C
Maximum charging current		5.4A
Maximum discharge current		270A(5 sec.)
Designed floating life(20°C)		5 years

Construction

Component	Positive plate	Negative plate	Container	Cover	Separator	Electrolyte	Safety valve	Terminal
Raw material	Lead dioxide	Lead	ABS	ABS	AGM	GEL	Rubber	Copper

Constant Current Discharge Characteristics (A, 25°C)


F.V/TIME	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	68.8	43.6	34.0	19.2	12.8	6.45	4.46	3.69	3.14	1.80	1.01
9.90V	66.7	42.3	33.2	18.8	12.6	6.41	4.44	3.67	3.12	1.80	1.01
10.2V	63.9	40.5	32.0	18.2	12.3	6.35	4.40	3.64	3.10	1.79	1.01
10.5V	61.2	38.8	30.9	17.8	12.7	6.26	4.37	3.62	3.08	1.78	1.00
10.8V	57.8	36.6	29.3	17.1	11.8	6.10	4.24	3.51	2.99	1.70	0.99

Constant Power Discharge Characteristics (Watt, 25°C)


F.V/TIME	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
9.60V	767	491	388	220	137	75.5	53.0	44.0	37.5	20.5	11.0
9.90V	744	477	379	215	134	75.0	52.7	43.7	37.3	20.4	10.9
10.2V	714	457	365	209	131	74.3	52.3	43.4	37.0	20.3	10.9
10.5V	683	437	352	204	128	73.2	52.0	43.1	36.8	20.2	10.8
10.8V	645	413	334	196	125	71.4	50.4	41.8	35.6	19.7	10.6

Note: The above characteristics data can be obtained within three charge/discharge cycles.


Discharge Characteristics(25℃)




Charging Characteristics(25℃)




Effect of Temperature on Capacity




Self-discharge Characteristics




Floating Life on Temperature



Cycle Life on D.O.D(25℃)



The Relationship for Open Circuit Voltage and Residual Capacity (25℃)



The Relationship for Charging Voltage and Temperature

